

Version 1.4	Revision Date: 03.06.2015	MSDS Number: 36406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014		
SECTION	N 1: Identification o	f the substance/n	nixture and of the company/undertakin		
1.1 Produ	uct identifier				
Trade	e name	: PURELL® Ac	: PURELL® Advanced Hygienic Hand Rub		
1.2 Relev	ant identified uses of	the substance or r	nixture and uses advised against		
Use	of the Sub- ce/Mixture	: Hand Sanitize	-		
1.3 Detail	s of the supplier of th	ne safety data shee	t i i i i i i i i i i i i i i i i i i i		
Comj	pany	: GOJO Indust Units 5 & 6, S MK10 0DE B	•		
Telep	ohone	: +44(0) 19085	88444		
Telef	ax	: +44(0) 19085	88445		
	ail address of person onsible for the SDS	: infoUK@gojo	.com		
	gency telephone num 0) 8445605135	ber			
SECTION	N 2: Hazards identif	ication			

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 127 Flammable liquids, Category 3	72/2008) H226: Flammable liquid and vapour.				
Eye irritation, Category 2	H319: Causes serious eye irritation.				
Classification (67/548/EEC, 1999/45/EC) Flammable Irritant	R10: Flammable. R36: Irritating to eyes.				
2.2 Label elements					

Labelling (REGULATION (EC) No 1272/2008)



Version 1.4	Revision Date: 03.06.2015		ISDS Number: 6406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014
Hazard pictograms		:		
Sign	al word	:	Warning	
Hazard statements		:	H226 H319	Flammable liquid and vapour. Causes serious eye irritation.
Prec	autionary statements	:	Prevention: P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
			P233 P280	Keep container tightly closed. Wear protective gloves/ protective clothing/ eye protection/ face protection.
			Response: P303 + P361 + P3	IF ON SKIN (or hair): Take off immedi- ately all contaminated clothing. Rinse skin with water/shower.
			P337 + P313	If eye irritation persists: Get medical advice/ attention.

2.3 Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Ethanol	64-17-5 200-578-6	F; R11 Xi; R36	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 50 - < 70
Propan-2-ol	67-63-0 200-661-7	F; R11 Xi; R36 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 3 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

: In the case of accident or if you feel unwell, seek medical advice immediately.



Version 1.4	Revision Date: 03.06.2015	MSDS Number:Date of last issue: 10.02.201536406-00005Date of first issue: 11.12.2014		
		When symptoms persist or in all cases of doubt seek medica advice.		
Protection of first-aiders		: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.		
lf inha	aled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.		
In case of skin contact		: Wash with water and soap as a precaution. Get medical attention if symptoms occur.		
In case of eye contact		In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.		
If swallowed		: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.		
4.2 Most i	mportant symptoms	and effects, both acute and delayed		
Risks		: Causes serious eye irritation.		
4.3 Indica	tion of any immediat	e medical attention and special treatment needed		
Treatment		: Treat symptomatically and supportively.		
SECTION	1 5: Firefighting me	asures		
-	juishing media			

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
5.2 Special hazards arising from	the	substance or mixture
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapours may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Carbon oxides



Version 1.4	Revision Date: 03.06.2015	MSDS Number: 36406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014		
5.3 Advice for firefighters Special protective equipment for firefighters		: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.			
Specific extinguishing meth- ods		cumstances an Use water spra	ing measures that are appropriate to local cir- id the surrounding environment. iy to cool unopened containers. naged containers from fire area if it is safe to do		

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equip- ment recommendations.
6.2 Environmental precautions		
Environmental precautions	:	Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so.

Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil
barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cle	aning up :	Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. For large spills, provide dyking or other appropriate contain- ment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor- bent. Local or national regulations may apply to releases and dis- posal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter- mine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding
		certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.



Version	Revision Date:	MSDS Number:	Date of last issue: 10.02.2015
1.4	03.06.2015	36406-00005	Date of first issue: 11.12.2014

SECTION 7: Handling and storage

7.1 Precautions for safe handling **Technical measures** : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. Local/Total ventilation : Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Advice on safe handling : Avoid inhalation of vapour or mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage : Keep in properly labelled containers. Keep tightly closed. areas and containers Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition. : Do not store with the following product types: Advice on common storage Strong oxidizing agents Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which in contact with water, emit flammable gases Explosives Gases 7.3 Specific end use(s)

Specific use(s)

: No data available



Version	Revision Date:	MSDS Number:	Date of last issue: 10.02.2015
1.4	03.06.2015	36406-00005	Date of first issue: 11.12.2014

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m3	GB EH40		
Further information	Where no sr	ecific short-term exp	osure limit is listed, a figur	e three times the		
		posure should be use				
Propan-2-ol	67-63-0	TWA		GB EH40		
Flupan-2-01	07-03-0	IVVA	400 ppm	GD EH40		
			999 mg/m3			
		STEL	500 ppm 1,250 mg/m3	GB EH40		
Derived No Effect L	_evel (DNEL)	according to Regula	ition (EC) No. 1907/2006	:		
Ethanol	:	End Use: Workers				
		Exposure routes: In	halation			
		•	ects: Acute local effects			
		Value: 1900 mg/m3				
		End Use: Workers	-			
		Exposure routes: SI	kin contact			
			ects: Long-term systemic e	effects		
		Value: 343 mg/kg k				
		End Use: Workers				
		Exposure routes: In	halation			
			ects: Long-term systemic e	effects		
		Value: 950 mg/m3	<u> </u>			
		End Use: Consume	rs			
		Exposure routes: In				
		Potential health effects: Acute local effects				
		Value: 950 mg/m3				
		End Use: Consume	rs			
		Exposure routes: SI				
			ects: Long-term systemic e	effects		
		Value: 206 mg/kg bw/day				
		End Use: Consumers				
		Exposure routes: In				
		Potential health effe	ects: Long-term systemic e	effects		
		Value: 114 mg/m3	C C C C C C C C C C			
		End Use: Consume	rs			
		Exposure routes: In				
			ects: Long-term systemic e	effects		
		Value: 87 mg/kg by				
Propan-2-ol	:	End Use: Workers				
		Exposure routes: In	halation			
		•	ects: Long-term systemic e	effects		
		Value: 500 mg/m3	č			
		End Use: Workers				
		Exposure routes: SI	kin contact			
		Potential health effects: Long-term systemic effects				
		Value: 888 mg/kg k				
			· · · · · · · · · · · · · · · · · · ·			



Version 1.4	Revision Date: 03.06.2015	MSDS Number: 36406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014
		Value: 89 mg/r End Use: Cons Exposure route Potential health Value: 319 mg End Use: Cons Exposure route Potential health Value: 26 mg/r	es: Inhalation n effects: Long-term systemic effects m3 sumers es: Skin contact n effects: Long-term systemic effects /kg bw/day sumers es: Ingestion n effects: Long-term systemic effects kg bw/day
		entration (PNEC) acco	rding to Regulation (EC) No. 1907/2006:
Ethan	ın-2-ol	 Fresh water Value: 0.96 mg Marine water Value: 0.79 mg Intermittent use Value: 2.75 mg Sewage treatm Value: 580 mg Fresh water se Value: 580 mg Fresh water se Value: 3.6 mg/ Marine sedime Value: 2.9 mg/ Soil Value: 0.63 mg Oral Value: 720 mg Fresh water Value: 140.9 m Marine water Value: 140.9 m Intermittent use Value: 140.9 m Sewage treatm Value: 2251 m Fresh water se Value: 552 mg 	g/l e/release g/l ent plant /l diment /kg nt /kg g/kg g/kg g/kg g/kg i/kg ng/l e/release ng/l ent plant g/l ent plant
		Marine sedime Value: 552 mg	
		Soil	***¥
		Value: 28 mg/l	κg
		Oral Value: 160 mg	/kg
8.2 Expos	ure controls		

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.

Personal protective equipment



Version 1.4	Revision Date: 03.06.2015	MSDS Number: 36406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014
Еуе р	rotection	: Wear the follo Safety goggle	wing personal protective equipment: s
	protection terial	: Impervious gl Flame retarda	
Re	marks	on the concer stance and sp determined fo applications, v chemicals of t	s to protect hands against chemicals depending htration and quantity of the hazardous sub- becific to place of work. Breakthrough time is not r the product. Change gloves often! For special we recommend clarifying the resistance to he aforementioned protective gloves with the cturer. Wash hands before breaks and at the ay.
Skin a	and body protection	sistance data tial. Wear the follo Flame retarda Skin contact r	riate protective clothing based on chemical re- and an assessment of the local exposure poten- wing personal protective equipment: ant antistatic protective clothing. nust be avoided by using impervious protective es, aprons, boots, etc).
Respi	ratory protection	tilation is prov	ry protection unless adequate local exhaust ven- ided or exposure assessment demonstrates that within recommended exposure guidelines.
Filt	er type	: Organic vapo	ur type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: clear
Odour	: alcohol-like
Odour Threshold	: No data available
рН	: 6.5 - 8.5
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: 24 °C
Evaporation rate	: No data available



Vers 1.4	sion	Revision Date: 03.06.2015		DS Number: 406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014
	Flamm	ability (solid, gas)	:	Not applicable	
	Upper	explosion limit	:	No data available	9
	Lower	explosion limit	:	No data available	9
	Vapou	r pressure	:	No data available	9
	Relativ	e vapour density	:	No data available	9
	Density	y	:	0.88 g/cm3	
	Solubil Wate	ity(ies) er solubility	:	soluble	
	Partitio octano	n coefficient: n- I/water	:	Not applicable	
	Auto-ig	nition temperature	:	No data available	9
	Decom	position temperature	:	The substance o	r mixture is not classified self-reactive.
	Viscos Visc	ity osity, kinematic	:	6,000 - 17,000 m	nm2/s (20 °C)
	Explos	ive properties	:	Not explosive	
	Oxidizi	ng properties	:	The substance o	r mixture is not classified as oxidizing.
0.2	Othor is	oformation			

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	: Flammable liquid and vapour.
	Vapours may form explosive mixture with air.
	Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials



/ersion I.4	Revision Date: 03.06.2015	MSDS Number: 36406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014
Mate	rials to avoid	: Oxidizing agen	ts
	ardous decomposition azardous decomposition		
SECTION	N 11: Toxicological in	formation	
	mation on toxicologica nation on likely routes of sure		
	e toxicity lassified based on availa	ble information.	
Com	ponents:		
Etha Acute	nol: e oral toxicity	: LD50 (Rat): > 5	,000 mg/kg
Acute	e inhalation toxicity	: LC50 (Rat): 124 Exposure time: Test atmospher	4 h
	an-2-ol: e oral toxicity	: LD50 (Rat): > 5	,000 mg/kg
Acute	e inhalation toxicity	: LC50 (Rat): 72. Exposure time: Test atmospher	4 h
Acute	e dermal toxicity	: LD50 (Rat): > 5	,000 mg/kg
Not c <u>Prod</u>	corrosion/irritation lassified based on availa <u>uct:</u> lt: No skin irritation	ble information.	
Etha Spec Meth	ponents: nol: ies: Rabbit od: OECD Test Guideline It: No skin irritation	e 404	
Spec	an-2-ol: ies: Rabbit It: No skin irritation		



Version	Revision Date:	MSDS Number:	Date of last issue: 10.02.2015
1.4	03.06.2015	36406-00005	Date of first issue: 11.12.2014

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Ethanol:

Species: Rabbit Method: OECD Test Guideline 405 Result: Irritation to eyes, reversing within 21 days

Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Components:

Ethanol:

Test Type: Local lymph node assay (LLNA) Exposure routes: Skin contact Species: Mouse Result: negative

Propan-2-ol:

Test Type: Buehler Test Exposure routes: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

Germ cell mutagenicity

Not classified based on available information.

<u>Components:</u> Ethanol:	
Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion Result: negative
Propan-2-ol:	
- · · · · · · ·	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo



sion	Revision Date: 03.06.2015	MSDS Number: 36406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014
		cytogenetic ass Species: Mous Application Rou Result: negativ	e ute: Intraperitoneal injection
Carci	nogenicity		
Not cl	assified based on avai	lable information.	
Propa Speci Applic Expos Metho	oonents: an-2-ol: es: Rat cation Route: inhalatior sure time: 104 weeks od: OECD Test Guideli t: negative		
•	oductive toxicity assified based on avai	lable information.	
<u>Comp</u>	oonents:		
Ethar Effect	nol: s on fertility	Species: Mous Application Ro	ute: Ingestion) Test Guideline 416
Propa	an-2-ol:		
	s on fertility	: Test Type: Two Species: Rat Application Rou Result: negativ	
Effect ment	s on foetal develop-	: Test Type: Em Species: Rat Application Ro Result: negativ	
	- single exposure		
	assified based on avai	lable information.	
	onents:		
Propa	an-2-ol:		

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components: Ethanol:



Version	Revision Date:	MSDS Number:	Date of last issue: 10.02.2015
1.4	03.06.2015	36406-00005	Date of first issue: 11.12.2014

Species: Rat NOAEL: 2,400 mg/kg Application Route: Ingestion Exposure time: 2 y

Propan-2-ol:

Species: Rat NOAEL: 5000 ppm Application Route: inhalation (vapour) Exposure time: 104 w Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

<u>Components:</u> Ethanol:		
Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to bacteria	:	EC50 (Photobacterium phosphoreum): 32.1 mg/l Exposure time: 0.25 h
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 9.6 mg/l Exposure time: 9 d Species: Daphnia magna (Water flea)
Propan-2-ol:		
Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to bacteria	:	EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h

12.2 Persistence and degradability

Components:



Version 1.4	Revision Date: 03.06.2015	MSDS Number: 36406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014		
Etl	hanol:				
Biodegradability		: Result: Readily I Biodegradation: Exposure time: 2	84 %		
Pre	opan-2-ol:				
	odegradability	: Result: rapidly d	: Result: rapidly degradable		
12.3 Bi	oaccumulative potential				
Co	mponents:				
	hanol:				
	rtition coefficient: n- tanol/water	: log Pow: -0.35			
Pa	opan-2-ol: rtition coefficient: n- tanol/water	: log Pow: 0.05			
	obility in soil data available				
12.5 Re	sults of PBT and vPvB a	ssessment			
	t relevant				
12.6 Other adverse effects No data available					
SECTI	SECTION 13: Disposal considerations				
13.1 W	aste treatment methods				
-	oduct	: Dispose of in ac	cordance with local regulations.		
			European Waste Catalogue, Waste Codes		

FIGUUCI	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Contaminated packaging	 Dispose of as unused product. Empty containers should be taken to an approved waste han- dling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1987
ADR	: UN 1987
RID	: UN 1987



Version 1.4	Revision Date: 03.06.2015	MSDS Number: 36406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014
IMDG	ì	: UN 1987	
ΙΑΤΑ		: UN 1987	
14.2 UN p	roper shipping name		
ADN		: ALCOHOLS, N. (Ethanol, Propar	
ADR		: ALCOHOLS, N. (Ethanol, Propar	O.S.
RID		: ALCOHOLS, N. (Ethanol, Propa	
IMDG	ì	: ALCOHOLS, N. (Ethanol, Propa	
ΙΑΤΑ		: Alcohols, n.o.s. (Ethanol, Propa	n-2-ol)
14.3 Trans	sport hazard class(es)		
ADN		: 3	
ADR		: 3	
RID		: 3	
IMDG	ì	: 3	
ΙΑΤΑ		: 3	
14.4 Pack	ing group		
ADN			
	ng group	:	
	ification Code rd Identification Number	: F1 : 30	
Label		: 3	
ADR			
	ng group	: 111	
	ification Code rd Identification Number	: F1 : 30	
Label		: 3	
Tunne	el restriction code	: (D/E)	
RID			
	ng group	:	
	ification Code rd Identification Number	: F1 : 30	
Label		: 3	
IMDG			
	ng group	:	
Label EmS		: 3 : F-E, S-D	
IATA		,	
	ng instruction (cargo	: 366	



Ver 1.4	sion	Revision Date: 03.06.2015		SDS Number: 406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014
	ger airc Packing	g instruction (passen-	:	355 Y344 III Flammable Liquic	ls
14.5 Environmental hazards					
	ADN Enviror	nmentally hazardous	:	no	
	ADR Enviror	nmentally hazardous	:	no	
	RID Enviror	nmentally hazardous	:	no	
	IMDG Marine	pollutant	:	no	
14.6 Special precautions for use Not applicable		er			

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks	: Not applicable for product as supplied.
	1.1 1 1.1

SECTION 15: Regulatory information

6

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Regulation (EC) No 649/2012 of the European Parlia- : Not applicable

Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EC) No 850/2004 on persistent organic pol- lutants	:	Not applicable
Seveso II - Directive 2003/105/EC amending Council Dire	ectiv	ve 96/82/EC on the conti

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of majoraccident hazards involving dangerous substances

	Quantity 1	Quantity 2
Flammable.	5,000 t	50,000 t

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of
major-accident hazards involving dangerous substances.
P5cP5cFLAMMABLE LIQUIDS5,000 t50,000 t34Petroleum products: (a)2,500 t25,000 t

gasolines and naphthas,



Version 1.4	Revision Date: 03.06.2015	MSDS Number: 36406-00005	Date of last issue: 10.02.2015 Date of first issue: 11.12.2014
		(b) kerosenes (fuels), (c) gas c ing diesel fuels, heating oils and blending strean heavy fuel oils of tive fuels servin purposes and w properties as re flammability and mental hazards products referre points (a) to (d)	ils (includ- home d gas oil hs),(d) (e) alterna- ig the same vith similar egards d environ- as the ed to in
Vola	atile organic compounds	emissions (inte	75/EU of 24 November 2010 on industrial grated pollution prevention and control) compounds (VOC) content: < 75 %
The	components of this pro	oduct are reported i	n the following inventories:

AICS : All ingredients listed or exempt.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

R11 R36 R67	:	Highly flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.		
Full text of H-Statements				
H225		Highly flammable liquid and vapour.		
H319	:	Causes serious eye irritation.		
H336	:	May cause drowsiness or dizziness.		
Full text of other abbreviations				
Full text of other abbreviation	าร			
Full text of other abbreviation Eye Irrit.		Eye irritation		
	:	Eye irritation Flammable liquids		
Eye Irrit.	:	Flammable liquids		
Eye Irrit. Flam. Liq.	:	Flammable liquids Specific target organ toxicity - single exposure		
Eye Irrit. Flam. Liq. STOT SE	:	Flammable liquids Specific target organ toxicity - single exposure UK. EH40 WEL - Workplace Exposure Limits		
Eye Irrit. Flam. Liq. STOT SE GB EH40	:	Flammable liquids Specific target organ toxicity - single exposure		

Further information



Version	Revision Date:	MSDS Number:	Date of last issue: 10.02.2015
1.4	03.06.2015	36406-00005	Date of first issue: 11.12.2014
	es of key data used to e the Safety Data		data, data from raw material SDSs, OECD arch results and European Chemicals Agen- ropa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN